

- 3. EROSION LOGS SHALL BE TIGHTLY ABUTTED WITH NO GAPS.
- 4. V-SHAPED TEMPORARY DITCHES SHALL NOT BE USED. DITCHES SHAL BE GRADED IN A PARABOLIC OR TRAPEZOIDAL SHAPE.

### **EROSION LOG INSTALLATION**

- 4. FOR SLOPE AND CHANNEL SPACING SEE THE "SECTION VIEW ALONG DITCH FLOWLINE" DETAIL ON SHEET 11 OF 11.
- 5. SOIL RETENTION BLANKET SHALL ALWAYS BE REQUIRED.
- 6. THE PAY ITEM NUMBER FOR SILT BERM (LF) IS 208-00004.

### SILT BERM INSTALLATION

## DRAINAGE DITCH APPLICATIONS

Computer File Information			Sheet Revisions		$\int_{C}$
Creation Date: 07/04/12	Initials: JBK		Date:	Comments	] `
Last Modification Date: 03/29/16	Initials: LTA	$\overline{\mathbb{R}-X}$			
Full Path: www.coloradodot.info/business/designsupport		$\overline{R-X}$			1 4
Drawing File Name: 2080106011.dgn		$\overline{R-X}$			֡֡֡֡֞֞֞֞֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡
CAD Ver.: MicroStation V8 Scale: Not to Scale	e Units: English	(R-X)			יו

## Colorado Department of Transportation

CDOT 4201 East Arkansas Avenue CDOT HQ, 4th Floor Denver, CD 80222 Phone: 303-757-9021 FAX: 303-757-9868 JBK/LTA Division of Project Support

# Issued By: Project Development Branch on July 4, 2012

STANDARD PLAN NO. M-208-1Sheet No. 6 of 11

5. THE PAY ITEM NUMBER FOR SILT DIKE (LF) IS 208-00001.

SILT DIKE INSTALLATION

**TEMPORARY EROSION CONTROL**